

# 2,000 GALLON GREASE INTERCEPTOR CITY OF HUNTSVILLE

MODEL: GI 2000/186

PRODUCT INFORMATION  
2,000 GALLON  
GREASE INTERCEPTOR

TANK= 21,170 #  
LID= 8,000 # BARTOW PRECAST  
DESIGN MAY VARY

SPECIFICATIONS  
MEETS ASTM C 1613

RATING: A-16 (H-20), ASSUME  
4" MAX EARTH COVER WITH 3"  
WATER TABLE BELOW GRADE

CONCRETE: 5,000 PSI @ 28 DAYS  
STEEL REINFORCEMENT: MEETS  
ASTM A 615, PLACEMENT AS  
REQUIRED BY DESIGN

INLET & OUTLET BOOT MEETS  
ASTM C 923, ACCEPTS 4" & 6" PVC

BUTYL SEALANT: MEETS ASTM  
C 900, USED ON JOINTS

ACCESS OPENING SUITABLE FOR  
24" RISER AND/OR RING & COVER  
INTERNAL PIPING BY OTHERS  
PER MUNICIPAL SPECS

BAFFLE CROSSOVER TO BE TWO  
6" PVC SLEEVES

CALL FOR ADDITIONAL SPECS



## DRAWING INFORMATION


Drawn By: JJG  
Checked By: 2  
Revision: 2  
Date: 2/7/14

APPROVED BY: \_\_\_\_\_

print: \_\_\_\_\_

sign: \_\_\_\_\_

\*actual dimensions may vary slightly



Scale: 1/4" = 1'



**BARTOW  
PRECAST**

770.382.4462  
sales@bartowprecast.com  
WWW.BARTOWPRECAST.COM