





7'x7'x6' (ID) Vault with Floor













770.382.4462 WWW.BARTOWPRECAST.COM sales@bartowprecast.com

SS120-60707 F L0808-3636

PRODUCT INFORMATION

7'x7'x6' (ID) UTILITY VAULT

*design may vary Vault = 18,100 # Lid = 4,100 #

SPECIFICATIONS MEETS ASTM C858 & C857

RATING: NON-TRAFFIC

CONCRETE TO BE 4,000 PSI @ 28 DAYS

REINFORCING STEEL MEETS ASTM A 615

10" STEPS ON 12" CENTERS

BUTYL SEALANT MEETING ASTM C 990 TO BE USED ON JOINTS

ALUMINUM DIAMOND PLATE DESIGNED TO SUPPORT 300 psf 36"x36" FRAME OPENING EQUIPPED WITH: SLAM LOCK, FLUSH MOUNT LIFT HANDLE, HOLD-OPEN ARM, SS HARDWARE AND HINGES ACCESS HATCH SHALL BE FABRICATED WITH 1/4"

PENETRATIONS SIZE AND LOCATION VARY PER JOB CALL FOR ADDITIONAL SPECS



DRAWING INFORMATION

Drawn By: Checked By: Date: Revision:

APPROVED BY:

| print:_ | |
|---------|--|
| | |
| | |
| | |

sign: *actual dimensions may vary slightly